



Premium Emulsion Paint for Exterior
TOA NANOCLEAN

<p>Description</p>	<p>TOA NanoClean is 100% Acrylic premium emulsion paint for interior. Apply Hybrid Nano technology to keep your house safely, fresh beauty and durability. Hybrid Nano technology combine the preeminent function of Nano Fluoro Carbon for easy washing and Nano Silver for complete Anti Bacteria.</p> <ul style="list-style-type: none"> • Nano Fluoro Carbon makes a protective layer in order to oil and water repellency therefore easy to clean the stain. • Nano Silver can kill bacteria to 99.9% <p>Otherwise , TOA NanoClean also have especial properties such as: smooth surface, anti fungus, good hiding, easy to touch up, good smell and long lasting color.</p>																		
<p>Typical Uses</p>	<p>It is suitable for application on the surface : plaster, concrete, brick, and any surfaces especially for area that requires extra hygiene example kitchen, children bedroom, alley, hallway, kindergarten and hospital v.v..</p>																		
<p>Physical Properties</p> <p>Component</p> <p>Performance Specification</p> <p>Drying Time</p> <p>Specific Gravity</p>	<table border="0"> <tr> <td>Pure Acrylic Binder, Nano Fluoro Carbon, Nano Silver</td> <td>72% approximately</td> </tr> <tr> <td>Water</td> <td>20% approximately</td> </tr> <tr> <td>Additive</td> <td>8% approximately</td> </tr> <tr> <td>Film Appearance</td> <td>2 finishes: Sheen, Hi sheen</td> </tr> <tr> <td>%Non Volatile</td> <td>49.5 - 50.5</td> </tr> <tr> <td>Coverage</td> <td>13-16 m²/litre/coat approx.</td> </tr> <tr> <td>Touch Dry</td> <td>30 mins</td> </tr> <tr> <td>Hard Dry</td> <td>2 hrs</td> </tr> <tr> <td>Specific Gravity</td> <td>1.28 - 1.31 g/cm³</td> </tr> </table>	Pure Acrylic Binder, Nano Fluoro Carbon, Nano Silver	72% approximately	Water	20% approximately	Additive	8% approximately	Film Appearance	2 finishes: Sheen, Hi sheen	%Non Volatile	49.5 - 50.5	Coverage	13-16 m ² /litre/coat approx.	Touch Dry	30 mins	Hard Dry	2 hrs	Specific Gravity	1.28 - 1.31 g/cm ³
Pure Acrylic Binder, Nano Fluoro Carbon, Nano Silver	72% approximately																		
Water	20% approximately																		
Additive	8% approximately																		
Film Appearance	2 finishes: Sheen, Hi sheen																		
%Non Volatile	49.5 - 50.5																		
Coverage	13-16 m ² /litre/coat approx.																		
Touch Dry	30 mins																		
Hard Dry	2 hrs																		
Specific Gravity	1.28 - 1.31 g/cm ³																		
<p>Application Method</p> <p>Tools</p> <p>Thinner</p>	<p>Brush, Spray, Roller</p> <p>Clean water 10 - 15% by Volume (Depend on application)</p>																		
<p>Application System</p> <p>Surface Preparation</p> <p>New Surface :</p> <p>Old Surface :</p> <p>Precaution :</p>	<p>Ensure the surface to be painted is clean, dry, free from dirt ,oil or other contamination. Must remove all loose or defective paint or powdery residue and fungus or algae. Repair the damaged areas. In the case: if there are splits larger than 0.1mm, they should be fixed and smoothed by TOA putty.</p> <p>Prime 1 coat of TOA NanoClean Int.Alkali Resisting Primer Then top coat with 2 coats of TOA Nanoclean</p> <p>Prime 1 coat of 4 Seasons Contact Sealer Then top coat with 2 coats of TOA Nanoclean</p> <ol style="list-style-type: none"> 1. Keep away from children and avoid contact with eyes. 2. Stir well before use and once opened, entire contents should be used. Store in a cool, shaded place. 3. Allow new surface to dry out around 21 -28 days in normal condition before painting. 4. Ensure correct primer and/or sealer is used and allow putty to thoroughly harden before painting 																		
<p>Disclaimer</p>	<p>This information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything only the quality of the product itself. We reserve the right to change the given data without notice.</p>																		